## NSN 5305-01-059-1956

Close Tolerance Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-059-1956

| Thread Olivery  |
|---|
| Thread Class:   |
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| Between 0.400 inches and 0.450 inches                                     |
| Fastener Length:  |
| Between 2.410 inches and 2.440 inches                                     |
| Head Style:   |
| Flat countersunk  |
| Head Diameter:  |
| Between 0.455 inches and 0.510 inches                                     |
| Grip Diameter:  |
| Between 0.2485 inches and 0.2495 inches                                   |
| Internal Drive Style:   |
| Cross recess type 1   |
| Thread Diameter:  |
| 0.250 inches  |
| Grip Length:  |
| Between 1.990 inches and 2.010 inches                                     |
| Thready Qty Per Inch (tpi):   |
| 28  |
| Countersink Angle:  |
| 100.0 degrees   |
| Surface Finish:   |
| 32.0 microinches threads  |
| Material:   |
| Steel comp e4340 or steel comp 8740                                       |
| Surface Treatment:  |
| Cadmium and chromate  |
| Surface Treatment Specification:  |
| Qq-p-416, type 2, class 2 federal specification single treatment response |
| Thread Series Designator:   |
| Unf   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| Νο  |
| Fiig:   |
| A003b0  |
|   |