NSN 5305-01-059-3576

Machine Screw - Page 1 of 2

Thread Class:

Thread Direction:

2a

View Online at https://aerobasegroup.com/nsn/5305-01-059-3576



Right-hand Thread Length: Between 0.035 inches and 0.077 inches Fastener Length: Between 0.094 inches and 0.125 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.244 inches and 0.279 inches **Head Height:** Between 0.048 inches and 0.059 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** 81.0 degrees **Screw Material:** Stainless steel **Screw Material Specification:** Qq-s-763, 300 series federal specification single material response or 66, 300 series federal standard single material response **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Mil-c-13924, cl 4 military specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 3 type and 2c style Shelf Life: N/a Unit Of Measure: **Demilitarization:** No

NSN 5305-01-059-3576

Machine Screw - Page 2 of 2

Fiig: A500d0

Mil-std (military Standard):

Mil-c-13924 spec.

