NSN 5305-01-059-4880

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-059-4880 **Thread Class:** 2b **Thread Direction:** Right-hand Thread Length: 0.160 inches **Fastener Length:** Between 0.545 inches and 0.575 inches **Head Style:** Pan no. 2 **Head Diameter:** 0.250 inches **Head Height:** 0.080 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 40 **Screw Material:** Steel **Screw Material Specification:** Qq-s-763, cl 300 federal specification single material response **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Mil-f-13924, cl 3 military specification single treatment response **Special Features:** Shank undercut to 0.080 in. Diameter 0.400 in. Lg below head binding surface **Test Data Document:** 98230-0n503175 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-059-4880

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-f-13924 spec.