NSN 5305-01-059-7432

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-059-7432

3a         Thread Direction:         Right-hand         Thread Length:         0.875 inches         Fastener Length:         Between 2.148 inches and 2.188 inches         Head Style:         Flat chamfer         Head Diameter:         Between 0.303 inches and 0.312 inches         Head Height:         Between 0.185 inches and 0.190 inches         Internal Drive Style:         Hexagon         Thread Diameter:         0.190 inches         Width Across Flats:         Between 0.1562 inches and 0.1587 inches         Thready Qty Per Inch (tpi):         24         Min. Tensile Strength (psi):         180000 pounds per square inch         Hardness Rating:         38.0 rockwell c and 45.0 rockwell c         Minimum Yield Strength:         155000 pounds per square inch         Product Name:         Navy special project         Material:         Steel         Striffect Treatment:         Oxide         Striffect Treatment:         Oxide         Striffect Treatment:         Oxide         Striffect Treatment Specification single treatment response	Thread Class:
Thread Direction:Right-handThread Length:0.875 inchesFastener Length:Between 2.148 inches and 2.188 inchesHead Style:Flat chamferHead Diameter:Between 0.303 inches and 0.312 inchesBetween 0.185 inches and 0.190 inchesHead Height:Between 0.185 inches and 0.190 inchesInternal Drive Style:HexagonThread Diameter:0.190 inchesWidth Across Flats:Between 0.1562 inches and 0.1587 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchProduct Name:Navy special projectMaterial:StrelSurface Treatment:CixideSurface Treatment:CixideMin-C-13924 class 1 military specification single treatment responseThread Series Designator:UnrcSpecification Data:	
Right-hand         Right-hand         Thread Length:         0.875 inches         Fastener Length:         Between 2.148 inches and 2.188 inches         Head Style:         Flat chamfer         Head Diameter:         Between 0.303 inches and 0.312 inches         Head Height:         Between 0.185 inches and 0.190 inches         Internal Drive Style:         Hexagon         Thread Diameter:         0.190 inches         Width Across Flats:         Between 0.1562 inches and 0.1587 inches         Thready Qty Per Inch (tpi):         24         Min. Tensile Strength (psi):         180000 pounds per square inch         Hardness Rating:         38.0 rockwell c and 45.0 rockwell c         Minimum Yield Strength:         155000 pounds per square inch         Product Name:         Navy special project         Material:         Steel         Strei         Strifece Treatment:         Oxide         Strifece Treatment Specification:         Mile-ch3924 class 1 military specification single treatment response         Thread Series Designator:         Unrc <td></td>	
Thread Length:0.875 inchesFastener Length:Between 2.148 inches and 2.188 inchesHead Style:Flat chamferHead Diameter:Between 0.303 inches and 0.312 inchesHead Height:Between 0.185 inches and 0.190 inchesInternal Drive Style:HexagonThread Diameter:0.190 inchesWidth Across Flats:Between 0.1562 inches and 0.1587 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c155000 pounds per square inchProduct Name:Navy special projectMaterial:SteelSteelSurface Treatment Specification single treatment responseThread Streis Designator:UnrcSpecification Data:	
0.875 inchesFastener Length:Between 2.148 inches and 2.188 inchesHead Style:Flat chamferHead Diameter:Between 0.303 inches and 0.312 inchesHead Height:Between 0.185 inches and 0.190 inchesInternal Drive Style:HexagonThread Diameter:0.190 inchesWidth Across Flats:Between 0.1562 inches and 0.1587 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell cStoop pounds per square inchProduct Name:Navy special projectMaterial:SteelSteelSurface Treatment Specification single treatment responseCixideCixideCixideSteries Designator:UnrcSpecification Data:	5
Fastener Length:Between 2.148 inches and 2.188 inchesHead Style:Flat chamferHead Diameter:Between 0.303 inches and 0.312 inchesHead Height:Between 0.185 inches and 0.190 inchesInternal Drive Style:HexagonThread Diameter:0.190 inchesWidth Across Flats:Between 0.1562 inches and 0.1587 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchProduct Name:Navy special projectMaterial:SteelSurface Treatment:OxideSurface Treatment Specification single treatment responseThread Series Designator:UnrcSpecification Data:	-
Between 2.14B inches and 2.18B inches         Head Style:         Flat chamfer         Head Diameter:         Between 0.303 inches and 0.312 inches         Head Height:         Between 0.185 inches and 0.190 inches         Internal Drive Style:         Hexagon         Thread Diameter:         0.190 inches         Width Across Flats:         Between 0.1562 inches and 0.1587 inches         Thready Qty Per Inch (tpi):         24         Min. Tensile Strength (psi):         180000 pounds per square inch         Hardness Rating:         38.0 rockwell c and 45.0 rockwell c         Minimum Yield Strength:         155000 pounds per square inch         Product Name:         Navy special project         Material:         Steel         Surface Treatment:         Oxide         Surface Treatment Specification:         Mil-c-13924 class 1 military specification single treatment response         Thread Series Designator:         Unrc         Specification Data:	
Head Style:Flat chamferHead Diameter:Between 0.303 inches and 0.312 inchesHead Height:Between 0.185 inches and 0.190 inchesInternal Drive Style:HexagonThread Diameter:0.190 inchesWidth Across Flats:Between 0.1562 inches and 0.1587 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchProduct Name:Navy special projectMaterial:SteelSurface Treatment:OxideSurface Treatment Specification single treatment responseThread Series Designator:UnrcSpecification Data:	-
Flat chamfer         Head Diameter:         Between 0.303 inches and 0.312 inches         Head Height:         Between 0.185 inches and 0.190 inches         Internal Drive Style:         Hexagon         Thread Diameter:         0.190 inches         Width Across Flats:         Between 0.1562 inches and 0.1587 inches         Thready Qty Per Inch (tpi):         24         Min. Tensile Strength (psi):         180000 pounds per square inch         Hardness Rating:         38.0 rockwell c and 45.0 rockwell c         Minimum Yield Strength         155000 pounds per square inch         Product Name:         Navy special project         Material:         Steel         Surface Treatment:         Oxide         Surface Treatment Specification single treatment response         Thread Series Designator:         Unrc         Specification Data:	
Head Diameter:         Between 0.303 inches and 0.312 inches         Head Height:         Between 0.185 inches and 0.190 inches         Internal Drive Style:         Hexagon         Thread Diameter:         0.190 inches         Width Across Flats:         Between 0.1562 inches and 0.1587 inches         Thready Qty Per Inch (tpi):         24         Min. Tensile Strength (psi):         180000 pounds per square inch         Hardness Rating:         38.0 rockwell c and 45.0 rockwell c         Minimum Yield Strength:         155000 pounds per square inch         Product Name:         Navy special project         Material:         Steel         Surface Treatment:         Oxide         Surface Treatment Specification         Mil-c-13924 class 1 military specification single treatment response         Thread Series Designator:         Unrc         Specification Data:	-
Between 0.303 inches and 0.312 inches Head Height: Between 0.185 inches and 0.190 inches Internal Drive Style: Hexagon Thread Diameter: 0.190 inches Width Across Flats: Between 0.1562 inches and 0.1587 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Product Name: Navy special project Material: Steel Surface Treatment: Oxide Surface Treatment Specification single treatment response Thread Series Designator: Unrc Unrc	
Head Height:Between 0.185 inches and 0.190 inchesInternal Drive Style:HexagonThread Diameter:0.190 inchesWidth Across Flats:Between 0.1562 inches and 0.1587 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchProduct Name:Navy special projectMaterial:SteelSurface Treatment:OxideSurface Treatment Specification:Mil-c-13924 class 1 military specification single treatment responseThread Series Designator:UnrcSpecification Data:	
Between 0.185 inches and 0.190 inchesInternal Drive Style:HexagonThread Diameter:0.190 inchesWidth Across Flats:Between 0.1562 inches and 0.1587 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchProduct Name:Navy special projectMaterial:SteelSurface Treatment:OxideSurface Treatment Specification single treatment responseThread Series Designator:UnrcSpecification Data:	
Internal Drive Style:HexagonThread Diameter:0.190 inchesWidth Across Flats:Between 0.1562 inches and 0.1587 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchProduct Name:Navy special projectMaterial:SteelSurface Treatment:OxideSurface Treatment Specification:Mil-c-13924 class 1 military specification single treatment responseThread Series Designator:UnrcSpecification Data:	-
HexagonThread Diameter:0.190 inchesWidth Across Flats:Between 0.1562 inches and 0.1587 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength155000 pounds per square inchProduct Name:Navy special projectMaterial:SteelSurface Treatment:OxideSurface Treatment SpecificationMil-c-13924 class 1 military specification single treatment responseInreUnrcSpecification Data:	
Thread Diameter:0.190 inchesWidth Across Flats:Between 0.1562 inches and 0.1587 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMininum Yield Strength:155000 pounds per square inchProduct Name:Navy special projectMaterial:SteelSurface Treatment:OxideSurface Treatment SpecificationMile-13924 class 1 military specification single treatment responseInreUnrcSpecification Data:	
0.190 inches Width Across Flats: Between 0.1562 inches and 0.1587 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Product Name: 155000 pounds per square inch Product Name: 155000 pounds per square inch Steel Surface Treatment: Oxide Surface Treatment Specification: Mil-c-13924 class 1 military specification single treatment response Thread Series Designator: Unrc	-
Width Across Flats:Between 0.1562 inches and 0.1587 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchProduct Name:Navy special projectMaterial:SteelSurface Treatment:OxideSurface Treatment SpecificationMil-c-13924 class 1 military specification single treatment responseThread Series Designator:UnrcSpecification Data:	
Between 0.1562 inches and 0.1587 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Product Name: 155000 pounds per square inch Product Name: Navy special project Material: Steel Surface Treatment: Oxide Surface Treatment Specification Mil-c-13924 class 1 military specification single treatment response Thread Series Designator: Unrc Specification Data:	
Thready Qty Per Inch (tpi):         24         Min. Tensile Strength (psi):         180000 pounds per square inch         Hardness Rating:         38.0 rockwell c and 45.0 rockwell c         Minimum Yield Strength:         155000 pounds per square inch         Product Name:         Navy special project         Material:         Steel         Surface Treatment:         Oxide         Surface Treatment Specification:         Mil-c-13924 class 1 military specification single treatment response         Thread Series Designator:         Unrc         Specification Data:	
24Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchProduct Name:Navy special projectMaterial:SteelSurface Treatment:OxideSurface Treatment Specification:Mil-c-13924 class 1 military specification single treatment responseThread Series Designator:UnrcSpecification Data:	
Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchProduct Name:Navy special projectMaterial:SteelSurface Treatment:OxideSurface Treatment Specification:Mil-c-13924 class 1 military specification single treatment responseThread Series Designator:UnrcSpecification Data:	Thready Qty Per Inch (tpi):
180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Product Name: Navy special project Material: Steel Surface Treatment: Oxide Surface Treatment Specification: Mil-c-13924 class 1 military specification single treatment response Thread Series Designator: Unrc Specification Data:	24
Hardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchProduct Name:Navy special projectMaterial:SteelSurface Treatment:OxideSurface Treatment Specification:Mil-c-13924 class 1 military specification single treatment responseThread Series Designator:UnrcSpecification Data:	Min. Tensile Strength (psi):
38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Product Name: Navy special project Material: Steel Surface Treatment: Oxide Surface Treatment Specification: Mil-c-13924 class 1 military specification single treatment response Thread Series Designator: Unrc Specification Data:	180000 pounds per square inch
Minimum Yield Strength: 155000 pounds per square inch Product Name: Navy special project Material: Steel Surface Treatment: Oxide Surface Treatment Specification: Mil-c-13924 class 1 military specification single treatment response Thread Series Designator: Unrc Specification Data:	Hardness Rating:
155000 pounds per square inch Product Name: Navy special project Material: Steel Surface Treatment: Oxide Surface Treatment Specification: Mil-c-13924 class 1 military specification single treatment response Thread Series Designator: Unrc Specification Data:	38.0 rockwell c and 45.0 rockwell c
Product Name:Navy special projectMaterial:SteelSurface Treatment:OxideSurface Treatment Specification:Mil-c-13924 class 1 military specification single treatment responseThread Series Designator:UnrcSpecification Data:	Minimum Yield Strength:
Navy special project Material: Steel Surface Treatment: Oxide Surface Treatment Specification: Mil-c-13924 class 1 military specification single treatment response Thread Series Designator: Unrc Specification Data:	155000 pounds per square inch
Material:SteelSurface Treatment:OxideSurface Treatment Specification:Mil-c-13924 class 1 military specification single treatment responseThread Series Designator:UnrcSpecification Data:	Product Name:
Steel Surface Treatment: Oxide Surface Treatment Specification: Mil-c-13924 class 1 military specification single treatment response Thread Series Designator: Unrc Specification Data:	Navy special project
Surface Treatment: Oxide Surface Treatment Specification: Mil-c-13924 class 1 military specification single treatment response Thread Series Designator: Unrc Specification Data:	Material:
Oxide Surface Treatment Specification: Mil-c-13924 class 1 military specification single treatment response Thread Series Designator: Unrc Specification Data:	Steel
Surface Treatment Specification: Mil-c-13924 class 1 military specification single treatment response Thread Series Designator: Unrc Specification Data:	Surface Treatment:
Mil-c-13924 class 1 military specification single treatment response Thread Series Designator: Unrc Specification Data:	Oxide
Thread Series Designator: Unrc Specification Data:	Surface Treatment Specification:
Unrc Specification Data:	Mil-c-13924 class 1 military specification single treatment response
Specification Data:	Thread Series Designator:
-	Unrc
80205-nac1352 professional/industrial association standard	Specification Data:
	80205-nas1352 professional/industrial association standard
Shelf Life:	Shelf Life:
N/a	N/a

## NSN 5305-01-059-7432

Socket Head Cap Screw - Page 2 of 2

AeroBase Group

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.