## NSN 5305-01-059-7436

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-059-7436

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.500 inches
Fastener Length:
Between 1.690 inches and 1.750 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.735 inches and 0.750 inches
Head Height:
Between 0.492 inches and 0.500 inches
Hole Diameter:
0.064 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.500 inches
Width Across Flats:
Between 0.375 inches and 0.379 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
170000 pounds per square inch
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
150000 pounds per square inch
Hole Configuration Style:
Round longitudinal hole
Material:
Steel
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response

## NSN 5305-01-059-7436

Socket Head Cap Screw - Page 2 of 2



**Thread Series Designator:** 

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0