NSN 5305-01-059-8670

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-059-8670 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.516 inches and 0.546 inches **Fastener Length:** 4.246 inches **First Diameter From Head:** Between 0.139 inches and 0.145 inches **Second Diameter From Head:** Between 0.159 inches and 0.165 inches **Third Diameter From Head:** Between 0.250 inches and 0.270 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.425 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 3.622 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Between 3.700 inches and 3.730 inches **Internal Drive Style:** Cross recess type ii **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 430 **Material Specification:** Qq-s-763 cond a federal specification single material response or qq-w-423 federal specification single material response **Surface Treatment:** Passivate grip **Surface Treatment Specification:** Qq-p-35 type 2 federal specification single treatment response grip **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-01-059-8670

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0