NSN 5305-01-060-9094

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-060-9094 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.310 inches and 0.330 inches **Fastener Length:** 1.060 inches **Head Style:** Flat chamfer **Head Diameter:** 0.490 inches **Head Height:** 0.250 inches **First Diameter From Head:** 0.380 inches **Second Diameter From Head:** 0.206 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.280 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.750 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Criticality Code Justification:** Zzzy **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 **Surface Treatment: Passivate Special Test Features:** Special quality control testing

Test Data Document:

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

NSN 5305-01-060-9094

Externally Relieved Body Screw - Page 2 of 2



Reference Number Differentiating Characteristics:

As differentiated by material which must conform to ships parts control center special quality control provisions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0