## NSN 5305-01-060-9094

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-060-9094 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.310 inches and 0.330 inches **Fastener Length:** 1.060 inches **Head Style:** Flat chamfer **Head Diameter:** 0.490 inches **Head Height:** 0.250 inches **First Diameter From Head:** 0.380 inches **Second Diameter From Head:** 0.206 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.280 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.750 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Criticality Code Justification:** Zzzy **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 **Surface Treatment: Passivate Special Test Features:** Special quality control testing

**Test Data Document:** 

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

## NSN 5305-01-060-9094

Externally Relieved Body Screw - Page 2 of 2



## **Reference Number Differentiating Characteristics:**

As differentiated by material which must conform to ships parts control center special quality control provisions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0