Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-061-2964

Thre	ad Class:
3a	
Thre	ad Direction:
Righ	t-hand
Thre	ad Length:
0.87	5 inches
Fast	ener Length:
Betw	een 1.210 inches and 1.250 inches
Head	d Style:
Flat	chamfer
Head	d Diameter:
Betw	een 0.303 inches and 0.312 inches
Head	d Height:
Betw	een 0.185 inches and 0.190 inches
Hole	Diameter:
0.04	7 inches
Loci	king Feature:
Strip	threads
Inter	nal Drive Style:
Hexa	agon
Thre	ad Diameter:
0.19	0 inches
Widt	h Across Flats:
Betw	een 0.156 inches and 0.159 inches
Hole	Quantity:
6	
Hole	Туре:
Drille	ed
Thre	ady Qty Per Inch (tpi):
24	
Min.	Tensile Strength (psi):
1800	00 pounds per square inch
Harc	Iness Rating:
38.0	rockwell c and 45.0 rockwell c
Mini	mum Yield Strength:
1550	00 pounds per square inch
Hole	Configuration Style:
Rour	nd longitudinal hole
Mate	erial:
Stee	
	ace Treatment:
Cadı	nium and chromate

NSN 5305-01-061-2964

Socket Head Cap Screw - Page 2 of 2



Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Thread Series Designator:

Unrc

Specification Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0