
## NSN 5305-01-061-4466

3a

6

Socket Head Cap Screw - Page 1 of 2





## **Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.470 inches and 0.562 inches Fastener Length: Between 0.532 inches and 0.562 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches Hole Diameter: 0.047 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.156 inches and 0.159 inches Hole Quantity: Hole Type: Drilled Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b **Minimum Yield Strength:** 30000 pounds per square inch Hole Configuration Style: Round longitudinal hole Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7 Surface Treatment: Passivate **Thread Series Designator:** Unrf

## NSN 5305-01-061-4466

Socket Head Cap Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

