

View Online at <https://aerobasegroup.com/nsn/5305-01-062-3674>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

1.120 inches

Fastener Length:

3.180 inches

Head Style:

Hexagon

Head Height:

0.380 inches

Width Between Flats:

0.937 inches

Hole Diameter:

Between 0.080 inches and 0.090 inches

Point Length:

0.440 inches

Point Diameter:

0.310 inches

First Diameter From Head:

Between 0.672 inches and 0.673 inches

Third Diameter From Head:

Between 0.672 inches and 0.673 inches

Fourth Diameter From Head:

0.540 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.180 inches and 0.190 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.435 inches and 0.535 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

Between 0.470 inches and 0.655 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

Between 0.630 inches and 0.815 inches

Point Style:

Dog

Internal Drive Style:

W/o internal drive

Thread Diameter:

0.625 inches

Hole Quantity:

3

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

18

Hole Configuration Style:

Hexagon corners

Externally Relieved Body Diameter Quantity:

4

Special Features:

First diameter after threads 1.060 in. Nom lth and 0.535 in. Min, 0.540 in. Maximum dia

Material:

Nickel alloy 400

Material Specification:

Qq-n-281 cl a federal specification single material response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0