## NSN 5305-01-062-6451

Setscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-062-6451

Thread Class
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.261 inches and 0.375 inches
Fastener Length:
Between 0.469 inches and 0.500 inches
Head Style:
Fillister
Head Diameter:
Between 0.292 inches and 0.313 inches
Head Height:
Between 0.123 inches and 0.130 inches
Hole Diameter:
0.046 inches
Point Length:
0.125 inches
Point Diameter:
Between 0.123 inches and 0.127 inches
Point Style:
Dog
Internal Drive Style:
Slot
Thread Diameter:
0.190 inches
Hole Quantity:
1
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Hole Configuration Style:
Round longitudinal hole
Criticality Code Justification:
Zzzy
Material:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384
Special Test Features:
Special quality control testing
Test Data Document:

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5305-01-062-6451

Setscrew - Page 2 of 2

A003b0



Inread Series Designator:
Unc
Reference Number Differentiating Characteristics:
As differentiated by packaging which must conform to ships partscontrol center special quality control provisions
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: