NSN 5305-01-063-2350

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-063-2350 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.875 inches **Fastener Length:** Between 1.022 inches and 1.062 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Hole Diameter:** 0.047 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.156 inches and 0.158 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Hardness Rating:** 80.0 rockwell c Minimum Yield Strength: 30000 pounds per square inch **Hole Configuration Style:** Round longitudinal hole Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7 **Surface Treatment: Passivate**

Thread Series Designator: Unrf

NSN 5305-01-063-2350

Socket Head Cap Screw - Page 2 of 2



Spec	cific	ation	Data:
------	-------	-------	-------

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0