## NSN 5305-01-063-2359

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-063-2359 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.378 inches and 0.428 inches **Fastener Length:** Between 0.700 inches and 0.730 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.477 inches and 0.492 inches **Head Height:** Between 0.140 inches and 0.150 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 24.0 rockwell c and 35.0 rockwell c **Surface Finish:** 32.0 microinches threads Material: Iron alloy 660 **Surface Treatment: Passivate Thread Series Designator:** Unjf **Specification Data:** 80205-nas1578 professional/industrial association standard

Shelf Life:

**Unit Of Measure:** 

N/a

## NSN 5305-01-063-2359

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0