## NSN 5305-01-063-3781

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-063-3781 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 2.800 inches and 3.625 inches **Fastener Length:** Between 6.800 inches and 7.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 1.479 inches and 1.500 inches **Head Height:** Between 0.988 inches and 1.000 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 1.000 inches Width Across Flats: Between 0.750 inches and 0.757 inches Thready Qty Per Inch (tpi): 8 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 6 type Shelf Life:

N/a **Unit Of Measure:** --

## NSN 5305-01-063-3781

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0