NSN 5305-01-063-5059

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-063-5059

Thread Class:
3a Thread Direction:
Right-hand
Thread Length: Between 0.378 inches and 0.428 inches
Fastener Length:
Between 0.826 inches and 0.856 inches
Head Style:
Pan no. 2
Head Diameter:
Between 0.477 inches and 0.492 inches
Head Height:
Between 0.140 inches and 0.150 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.250 inches
Grip Length:
Between 0.428 inches and 0.448 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
24.0 rockwell c and 35.0 rockwell c
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Surface Treatment:
Passivate
Thread Series Designator:
Unjf
Specification Data:
80205-nas1578 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5305-01-063-5059

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

