NSN 5305-01-063-5810



Setscrew - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-063-5810 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.425 inches and 0.446 inches **Fastener Length:** Between 0.579 inches and 0.609 inches **Head Style:** Headless (setscrew) **Locking Feature:** Strip threads Point Length: Between 0.054 inches and 0.075 inches **Point Style:** Flat **Internal Drive Style:** Hexagon **Thread Diameter:** 0.375 inches Width Across Flats: Between 0.187 inches and 0.189 inches **Features Provided:** Casehardened Thready Qty Per Inch (tpi): 24 Hardness Rating: 28.0 rockwell c and 34.0 rockwell c **Point Chamfer Angle:** Between 80.0 degrees and 90.0 degrees Material: Steel comp 4140 or steel comp 8640 or steel comp 8740 **Material Specification:** Qq-s-624 federal specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:**

Unf

Shelf Life:

N/a

NSN 5305-01-063-5810

Setscrew - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0