NSN 5305-01-063-7945

Socket Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-063-7945

| Thread C | Class: |
|----------------------|--|
| 3a | |
| Thread D | Direction: |
| Right-har | nd |
| Thread L | ength: |
| 0.774 inc | hes |
| Fastener | Length: |
| 0.880 inc | hes |
| Head Sty | /le: |
| Flat coun | tersunk |
| Head Dia | ameter: |
| Between | 0.491 inches and 0.507 inches |
| Locking | Feature: |
| Strip thre | ads |
| Internal I | Drive Style: |
| Cross rec | cess type iii |
| Thread D | Diameter: |
| 0.250 inc | hes |
| Thready | Qty Per Inch (tpi): |
| 28 | |
| Counters | sink Angle: |
| 100.0 deg | grees |
| Material: | |
| Steel | |
| Material | Specification: |
| Mil-s-783 | 9 military specification single material response |
| Surface | Treatment: |
| Cadmium | 1 |
| Surface ⁻ | Treatment Specification: |
| Qq-p-416 | 6, type 2, class 3 federal specification single treatment response |
| Thread S | Series Designator: |
| Unf | |
| Shelf Life | e: |
| N/a | |
| Unit Of N | leasure: |
| | |
| Demilitar | rization: |
| No | |
| Fiig: | |
| A003b0 | |
| Mil-std (r | military Standard): |
| Mil-s-783 | 9 spec. |