

View Online at <https://aerobasegroup.com/nsn/5305-01-064-4049>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.626 inches and 1.750 inches

Fastener Length:

Between 1.688 inches and 1.750 inches

Head Style:

Pan

Head Diameter:

Between 0.306 inches and 0.322 inches

Head Height:

Between 0.105 inches and 0.115 inches

Locking Feature:

Patch threads

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Surface Finish:

32.0 microinches threads

Material:

Steel comp 4140 fastener or steel comp 4340 fastener or steel comp 8740 fastener

Material Specification:

Mil-s-5626 military specification 1st material response fastener or mil-s-8844 military specification 2nd material response fastener or ams6414 assn standard 2nd material response fastener or mil-s-6049 military specification 3rd material response fastener

Surface Treatment:

Cadmium fastener and chromate fastener

Surface Treatment Specification:

Qq-p-416 ty2 cl2 federal specification single treatment response fastener

Thread Series Designator:

Unjc

Specification Data:

80205-nas1190 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.