NSN 5305-01-064-4062

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-064-4062 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.523 inches and 0.559 inches **Fastener Length:** Between 1.164 inches and 1.184 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.704 inches and 0.762 inches **Locking Feature:** Detent ball grip **Grip Diameter:** Between 0.3737 inches and 0.3742 inches **Shank Unthreaded Hole Diameter:** 0.106 inches first hole and 0.116 inches first hole **Internal Drive Style:** High-torque **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.625 inches and 0.641 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** 100.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 1.036 inches first hole and 1.056 inches first hole **Surface Finish:** 32.0 microinches grip **Product Name:** Navy special project Material: Steel comp 630 **Surface Treatment: Passivate Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5305-01-064-4062

Close Tolerance Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0