Assembled Washer Screw - Page 1 of 2





**Thread Class:** 2a **Thread Direction: Right-hand Thread Length:** Between 0.555 inches and 0.625 inches Fastener Length: Between 0.605 inches and 0.625 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches Washer Quantity: 2 **Internal Drive Style:** Cross recess type ia **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Secondary Washer Relationship To Primary Washer: Not identical Secondary Washer Style: Flat **Primary Washer Outside Diameter:** Between 0.195 inches and 0.208 inches Secondary Washer Outside Diameter: Between 0.245 inches and 0.250 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.031 inches **Secondary Washer Material Thickness:** Between 0.017 inches and 0.025 inches **Special Features:** One washer phospher bronze and one washer brass Material: Copper alloy 360 **Surface Treatment:** Nickel

## NSN 5305-01-064-5438

Assembled Washer Screw - Page 2 of 2



**Thread Series Designator:** 

Unc

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0