

View Online at <https://aerobasegroup.com/nsn/5305-01-065-7394>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.330 inches and 0.380 inches

**Fastener Length:**

Between 0.860 inches and 0.890 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.266 inches and 0.286 inches

**Shoulder Diameter:**

0.193 inches first shoulder and 0.195 inches first shoulder

**Shoulder Length:**

0.510 inches first shoulder and 0.530 inches first shoulder

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

33.0 rockwell c and 37.0 rockwell c

**Countersink Angle:**

100.0 degrees

**Shoulder Shape:**

Round first shoulder

**Product Name:**

Screw, shoulder

**Material:**

Steel comp 4037 or steel comp 8740

**Material Specification:**

Aisi assn standard all material responses

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 ty2 class 3 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0