## NSN 5305-01-066-4050

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-066-4050 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.213 inches and 0.223 inches **Fastener Length:** 0.843 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **First Diameter From Head:** Between 0.140 inches and 0.145 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.620 inches and 0.630 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Iron alloy 660 **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 cl 4 black military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5305-01-066-4050

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.