Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-066-4050

Fhread Class:	
2a	
Fhread Direction:	
Right-hand	
Fhread Length:	
Between 0.213 inches and 0.223 inches	
Fastener Length:	
).843 inches	
lead Style:	
Pan	
lead Diameter:	
Between 0.357 inches and 0.373 inches	
Head Height:	
Between 0.122 inches and 0.133 inches	
First Diameter From Head:	
Between 0.140 inches and 0.145 inches	
Distance From Largest Bearing Surface Of Head To End Of First Diameter:	:
Between 0.620 inches and 0.630 inches	
nternal Drive Style:	
Cross recess type 1	
Thread Diameter:	
0.190 inches	
Fhready Qty Per Inch (tpi):	
32	
Min. Tensile Strength (psi):	
160000 pounds per square inch	
Externally Relieved Body Diameter Quantity:	
I Contraction of the second	
Material:	
ron alloy 660	
Surface Treatment:	
Dxide	
Surface Treatment Specification:	
Ail-c-13924 cl 4 black military specification single treatment response	
Fhread Series Designator:	
Jnf	
Shelf Life:	
۷/a	
Jnit Of Measure:	
<u>-</u>	
Demilitarization:	

Externally Relieved Body Screw - Page 2 of 2



Fiig: A003b0

Mil-std (military Standard):

Mil-c-13924 spec.