NSN 5305-01-066-4051

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-066-4051 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.215 inches and 0.225 inches **Fastener Length:** 0.445 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** Between 0.086 inches and 0.096 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.230 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Stainless steel **Material Specification:** Qq-s-763 300 series federal specification single material response or 66 300 series federal standard single material response or comp 16-18 or 18-8 assn standard single material response **Surface Treatment:** Passivate and oxide **Surface Treatment Specification:** Qq-p-35 ty+2 federal specification single treatment response and mil-c-13924 cl 4 black military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-066-4051

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.