NSN 5305-01-066-4443



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-066-4443 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.421 inches and 0.453 inches **Fastener Length:** Between 0.801 inches and 0.828 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.421 inches and 0.453 inches **Head Height:** Between 0.202 inches and 0.234 inches **Shoulder Diameter:** 0.311 inches first shoulder and 0.312 inches first shoulder **Shoulder Length:** 0.375 inches first shoulder and 0.380 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.140 inches and 0.172 inches Thready Qty Per Inch (tpi): 20 Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel comp 1137 **Material Specification:** Qq-s-637 federal specification single material response **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 class 1 military specification single treatment response **Thread Series Designator:** Unc

Shelf Life:

N/a

NSN 5305-01-066-4443

Shoulder Screw - Page 2 of 2



| U | nit | Of | Measure: |
|---|-----|----|----------|
| | | | |

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.