NSN 5305-01-066-5308

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-066-5308 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.331 inches **Fastener Length:** 0.831 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.376 inches and 0.385 inches **Grip Diameter:** Between 0.2016 inches and 0.2026 inches Single Shear Strength: 132000 pounds per square inch **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches **Grip Length:** 0.500 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c **Countersink Angle:** 100.0 degrees Material: Steel **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mac ps-13145 fscm 76301 mfr ref all treatment responses **Thread Series Designator:** Unjf

Shelf Life:

N/a

NSN 5305-01-066-5308

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0