NSN 5305-01-067-2418

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-067-2418 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.403 inches **Fastener Length:** Between 0.576 inches and 0.606 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.350 inches and 0.399 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.178 inches and 0.198 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Nas672 assn standard single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-067-2418

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0