
NSN 5305-01-067-3401

Close Tolerance Screw - Page 1 of 2





| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.314 inches and 0.364 inches |
| Fastener Length: |
| Between 1.574 inches and 1.604 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.339 inches and 0.381 inches |
| Grip Diameter: |
| Between 0.1890 inches and 0.1895 inches |
| Internal Drive Style: |
| High-torque |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 1.240 inches and 1.260 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Titanium alloy |
| Material Specification: |
| Nas 621 comp 6al-4v assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas663 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 5305-01-067-3401

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

