NSN 5305-01-067-5196

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-067-5196

Threa	nd Class:
3a	
Threa	d Direction:
Right-	hand
Threa	nd Length:
Betwe	een 0.337 inches and 0.387 inches
Faste	ner Length:
Betwe	een 0.472 inches and 0.502 inches
Head	Style:
Flat c	ountersunk
Head	Diameter:
Betwe	een 0.258 inches and 0.305 inches
Grip [Diameter:
Betwe	een 0.1885 inches and 0.1895 inches
Interr	nal Drive Style:
Offse	t cruciform (torque set)
Threa	Id Diameter:
0.190	inches
Grip l	Length:
Betwe	een 0.115 inches and 0.135 inches
Threa	idy Qty Per Inch (tpi):
32	
Min. T	Гensile Strength (psi):
16000	00 pounds per square inch
Coun	tersink Angle:
Betwe	een 99.0 degrees and 101.0 degrees
Surfa	ce Finish:
32.0 r	nicroinches threads
Mater	ial Specification:
Ams {	5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single
mater	ial response
Surfa	ce Treatment:
Passi	vate
Surfa	ce Treatment Specification:
Qq-p-	35 federal specification single treatment response
Threa	nd Series Designator:
Unjf	
Speci	ification Data:
80205	5-nas1581 professional/industrial association standard
Shelf	Life:
N/a	
Unit (Of Measure:

NSN 5305-01-067-5196

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

