NSN 5305-01-067-6999

Unit Of Measure:

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-067-6999 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.200 inches **Fastener Length:** Between 0.470 inches and 0.500 inches **Head Style:** Fillister **Head Diameter:** Between 0.255 inches and 0.270 inches **Head Height:** 0.075 inches **First Diameter From Head:** Between 0.095 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.270 inches and 0.300 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Color black no. 37038 per federal std-595 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Tt-e-527 federal specification 1st treatment response head and mil-p-8585 military specification 2nd treatment response head **Thread Series Designator:** Unc Shelf Life: N/a

NSN 5305-01-067-6999

Externally Relieved Body Screw - Page 2 of 2



Demi			

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-p-8585 spec.