## NSN 5305-01-067-7001

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-067-7001 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.490 inches and 0.500 inches **Fastener Length:** 2.060 inches **Head Style:** Knurled no. 4 **Head Diameter:** Between 0.620 inches and 0.630 inches **Head Height:** Between 0.675 inches and 0.705 inches **First Diameter From Head:** Between 0.275 inches and 0.285 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.302 inches and 1.322 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): **Criticality Code Justification:** Zzzy **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Special Test Features:** Special quality control testing **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Test Data Document:** 

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Thread Series Designator:**

Unc

# NSN 5305-01-067-7001

Externally Relieved Body Screw - Page 2 of 2



#### **Reference Number Differentiating Characteristics:**

As differentiated by material which must conform to ships parts control center special quality control provisions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0