

View Online at <https://aerobasegroup.com/nsn/5305-01-067-8514>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.870 inches and 1.000 inches

**Fastener Length:**

Between 0.970 inches and 1.000 inches

**Head Style:**

Watertight

**Head Diameter:**

Between 0.473 inches and 0.517 inches

**Head Height:**

Between 0.162 inches and 0.175 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.250 inches

**Features Provided:**

O ring

**Thready Qty Per Inch (tpi):**

20

**Screw Material:**

Steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7

**Screw Material Specification:**

Qq-s-763 federal specification 1st material response or qq-s-763 federal specification 2nd material response or qq-s-763 federal specification 3rd material response or astm a 493 assn standard 1st material response or astm a493 assn standard 2nd material response or astm a 493 assn standard 3rd material response or astm a 493 assn standard 4th material response or astm a493 assn standard 5th material response

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Specification Data:**

80205-nas-3212 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0