## NSN 5305-01-067-9652

Shoulder Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-067-9652



## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.439 inches and 0.516 inches Fastener Length: Between 1.204 inches and 1.251 inches **Head Style:** Pan **Head Diameter:** Between 0.419 inches and 0.492 inches **Head Height:** Between 0.162 inches and 0.175 inches Shoulder Diameter: 0.213 inches first shoulder and 0.216 inches first shoulder Shoulder Length: 0.735 inches first shoulder and 0.765 inches first shoulder **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch Shoulder Shape: Round first shoulder **Product Name:** Navy special project Material: Iron alloy 660 Surface Treatment: Passivate Surface Treatment Specification: Ef43-1, fsc-82340 mfr ref single treatment response **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure:

---

## NSN 5305-01-067-9652

Shoulder Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

