NSN 5305-01-068-0485

Shoulder Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-068-0485

| I | nread Direction: |
|----|--|
| Ri | ight-hand |
| He | ead Style: |
| Fl | at chamfer |
| Sł | houlder Diameter: |
| 0. | 625 inches first shoulder |
| Sł | houlder Length: |
| 1. | 500 inches first shoulder |
| He | ole Diameter: |
| 0. | 141 inches |
| In | ternal Drive Style: |
| He | exagon |
| Tł | nread Diameter: |
| 0. | 500 inches |
| He | ole Quantity: |
| 1 | |
| He | ole Type: |
| Dı | rilled |
| Tł | nready Qty Per Inch (tpi): |
| 13 | 3 |
| He | ole Configuration Style: |
| R | bund |
| Sł | noulder Shape: |
| R | ound first shoulder |
| M | aterial: |
| St | eel |
| Sı | urface Treatment: |
| 0 | xide |
| Sı | urface Treatment Specification: |
| Ar | ms2485 assn standard single treatment response |
| Sł | helf Life: |
| N/ | 'a |
| Uı | nit Of Measure: |
| | |
| De | emilitarization: |
| N | 0 |
| Fi | ig: |