## NSN 5305-01-068-0787

Thumbscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-068-0787

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.150 inches and 0.200 inches
Fastener Length:
Between 1.400 inches and 1.450 inches
Head Style:
Knurled no. 4
Head Diameter:
0.380 inches
Head Height:
0.500 inches
First Diameter From Head:
Between 0.086 inches and 0.098 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
1.250 inches
Point Style:
Flat
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Externally Relieved Body Diameter Quantity:
1
Color:
Black
Material:
Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or
steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or
steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385
Material Specification:
Qq-s-763 federal specification all material responses
Surface Treatment:
Oxide
Surface Treatment Specification:
Mil-c-13924 military specification single treatment response
Thread Series Designator:
Unc

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5305-01-068-0787

Thumbscrew - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.