

View Online at <https://aerobasegroup.com/nsn/5305-01-068-0787>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.150 inches and 0.200 inches

Fastener Length:

Between 1.400 inches and 1.450 inches

Head Style:

Knurled no. 4

Head Diameter:

0.380 inches

Head Height:

0.500 inches

First Diameter From Head:

Between 0.086 inches and 0.098 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

1.250 inches

Point Style:

Flat

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

1

Color:

Black

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Material Specification:

Qq-s-763 federal specification all material responses

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.