## NSN 5305-01-068-2306

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-068-2306 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 2.310 inches and 2.500 inches **Fastener Length:** Between 2.410 inches and 2.500 inches **Head Style:** Pan **Head Diameter:** Between 0.473 inches and 0.492 inches **Head Height:** Between 0.162 inches and 0.175 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 125000 pounds per square inch **Screw Material:** Steel comp 403 or steel comp 405 or steel comp 410 or steel comp 414 or steel comp 416 or steel comp 420 **Screw Material Specification:** 66 federal standard all material responses **Screw Surface Treatment:** Passivate and zinc **Screw Surface Treatment Specification:** Qq-p-35, type 2 or type 3 federal specification 1st treatment response and qq-z-325, type 2 cl 3 federal specification 2nd treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A500d0