## NSN 5305-01-068-2321

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-068-2321

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.658 inches and 0.750 inches
Fastener Length:
Between 0.720 inches and 0.750 inches
Head Style:
Button
Head Diameter:
Between 0.250 inches and 0.262 inches
Head Height:
Between 0.063 inches and 0.073 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.138 inches
Width Across Flats:
0.078 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Material:
Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7
Material Specification:
66 federal standard 1st material response or 66 federal standard 2nd material response or 66 federal standard 3rd material response or 66
federal standard 4th material response or 66 federal standard 5th material response or astm a493 assn standard 6th material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unrc
Specification Or Standard:
8 type
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5305-01-068-2321

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0