## NSN 5305-01-068-5467

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-068-5467

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.125 inches
Fastener Length:
0.365 inches
Head Style:
Pan no. 2
Head Diameter:
Between 0.205 inches and 0.219 inches
Head Height:
Between 0.070 inches and 0.080 inches
First Diameter From Head:
Between 0.080 inches and 0.082 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.240 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
40
Externally Relieved Body Diameter Quantity:
1
Material:
Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel
comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 303 or steel comp 303se
Material Specification:
Qq-s-763 federal specification 1st material response or qq-s-763 federal specification 2nd material response or qq-s-763 federal
specification 3rd material response or qq-s-763 federal specification 4th material response or qq-s-763 federal specification 5th material
response or qq-s-763 federal specification 6th material response or qq-s-763 federal specification 7th material response or qq-s-763
federal specification 8th material response or qq-s-763 federal specification 9th material response or qq-s-763 federal specification 10th
material response or qq-s-763 federal specification 11th material response or astm a582 assn standard 12th material response or astm
a582 assn standard 13th material response
Surface Treatment:
Passivate
Surface Treatment Specification:

N/a

Unc

Shelf Life:

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

## NSN 5305-01-068-5467

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0