

View Online at <https://aerobasegroup.com/nsn/5305-01-068-8461>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.121 inches and 0.188 inches

**Fastener Length:**

Between 0.157 inches and 0.188 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.145 inches and 0.161 inches

**Head Height:**

Between 0.061 inches and 0.070 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.099 inches

**Thready Qty Per Inch (tpi):**

56

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Screw Material:**

Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347

**Screw Material Specification:**

Qq-s-763 federal specification all material responses

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0