Socket Head Cap Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-069-0508

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 1.375 inches and 1.500 inches |
| Fastener Length: |
| Between 1.438 inches and 1.500 inches |
| Head Style: |
| Pan |
| Head Diameter: |
| Between 0.306 inches and 0.322 inches |
| Head Height: |
| Between 0.105 inches and 0.115 inches |
| Locking Feature: |
| Patch threads |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.164 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| 36.0 rockwell c and 40.0 rockwell c |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp e4340 |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416 type 2, cl 2 federal specification single treatment response |
| Thread Series Designator: |
| Unjc |
| Specification Data: |
| 80205-nas1190 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5305-01-069-0508

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

