
## NSN 5305-01-069-0518

Close Tolerance Screw - Page 1 of 2





## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.313 inches and 0.363 inches Fastener Length: Between 0.448 inches and 0.478 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.328 inches and 0.385 inches Locking Feature: Strip threads **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches Grip Length: Between 0.115 inches and 0.135 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Plastic locking feature **Material Specification:** Ams5737 assn standard single material response fastener Surface Treatment: Passivate fastener **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response fastener **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1163 professional/industrial association standard

## NSN 5305-01-069-0518

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

