## NSN 5305-01-069-5224

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-069-5224 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.218 inches and 0.310 inches **Fastener Length:** Between 0.280 inches and 0.310 inches **Head Style:** Hexagon **Head Height:** Between 0.080 inches and 0.093 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Internal Drive Style:** Tri-wing recess **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams5731 assn standard single material response or ams5737 assn standard single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response **Special Features:** Green dye or paint on thd end for identification **Thread Series Designator:** Unjc **Specification Data:** 80205-nas6001 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## **NSN 5305-01-069-5224** Machine Screw - Page 2 of 2



Fiig:

A500d0