NSN 5305-01-069-7551



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-069-7551 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.234 inches and 0.254 inches **Fastener Length:** Between 0.303 inches and 0.321 inches **Head Style:** Double hexagon w/ hole **Head Height:** Between 0.220 inches and 0.240 inches Width Between Flats: Between 0.181 inches and 0.189 inches **Extended Washer Diameter:** Between 0.260 inches and 0.280 inches **Extended Washer Thickness:** Between 0.030 inches and 0.040 inches **Hole Diameter:** 0.047 inches **Thread Diameter:** 0.138 inches **Hole Quantity:** Thready Qty Per Inch (tpi): 40 Hardness Rating: Between 42.0 rockwell c and 46.0 rockwell c **Screw Material:** Steel **Screw Material Specification:** Ams630 assn standard single material response **Screw Surface Treatment:** Nickel and cadmium **Screw Surface Treatment Specification:** Ams2416 assn standard all treatment responses **Head Hole Configuration Style:** Double hexagon longitudinal hole **Thread Series Designator:**

Unjf
Shelf Life:

N/a

NSN 5305-01-069-7551

Machine Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A500d0