NSN 5305-01-069-8234



Machine Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-069-8234 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.720 inches and 0.795 inches **Fastener Length:** Between 1.047 inches and 1.092 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.932 inches and 1.022 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.500 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037 **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas517 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A500d0