## NSN 5305-01-070-1708

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-070-1708 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.283 inches and 0.333 inches **Fastener Length:** Between 0.741 inches and 0.771 inches **Head Style:** Hexagon **Head Height:** Between 0.367 inches and 0.376 inches Width Between Flats: Between 0.109 inches and 0.141 inches **Shoulder Diameter:** 0.189 inches first shoulder and 0.190 inches first shoulder **Shoulder Length:** 0.438 inches first shoulder and 0.458 inches first shoulder **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Shoulder Shape:** Round first shoulder Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5305-01-070-1708

Shoulder Screw - Page 2 of 2



Fiig:

A003b0