## NSN 5305-01-070-2058

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-070-2058 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.314 inches and 0.364 inches **Fastener Length:** Between 5.449 inches and 5.479 inches **Head Style:** Pan **Head Diameter:** Between 0.360 inches and 0.374 inches **Head Height:** Between 0.115 inches and 0.125 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Product Name:** Navy special project **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1218 professional/industrial association standard Shelf Life: N/a

No

**Unit Of Measure:** 

Demilitarization:

## NSN 5305-01-070-2058

Machine Screw - Page 2 of 2



Fiig:

A500d0