NSN 5305-01-070-5609

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-070-5609

View Online at https://aerobasegroup.com/nsn/5305-01-070-5609
Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 0.670 inches and 0.710 inches
Head Style:
Knurled no. 4
Head Diameter:
Between 0.405 inches and 0.435 inches
Head Height:
Between 0.275 inches and 0.305 inches
Material Accommodated Thickness:
Between 0.063 inches and 0.125 inches
Thread Diameter:
0.164 inches
Thready Qty Per Inch (tpi):
32
Criticality Code Justification:
Zzzy
Material:
Steel comp 302 spring
Material Specification:
Qq-w-423 cond b federal specification single material response spring
Surface Treatment:
Passivate spring
Special Test Features:
Special quality control testing
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response spring
Test Data Document:
81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unc
Reference Number Differentiating Characteristics:
As differentiated by packaging which must conform to ships parts control center special quality control provisions
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5305-01-070-5609

Panel Screw Assembly - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-a-8625 spec.