

View Online at <https://aerobasegroup.com/nsn/5305-01-070-7101>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.121 inches and 0.187 inches

Fastener Length:

Between 0.157 inches and 0.187 inches

Head Style:

Button

Head Diameter:

Between 0.154 inches and 0.164 inches

Head Height:

Between 0.038 inches and 0.046 inches

Locking Feature:

Patch threads or pellet threads

Internal Drive Style:

Hexagon

Thread Diameter:

0.086 inches

Width Across Flats:

0.050 inches

Thready Qty Per Inch (tpi):

56

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Surface Treatment:

Passivate

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0